



Finish Kare

"The Choice of Professionals Since 1964"

1726 Floradale Ave., So. El Monte, CA 91733
626-443-8983 & Fax: 626-443-0288

www.FinishKare.com



PRODUCT DATA SHEET FOR # 69: LIQUID RELEASE & STRIPPER

PRODUCT DESCRIPTION

69 is formulated specifically for the reinforced fiberglass and plastic industry to relieve the problem of wax build up and over spray on mold surface. It incorporates the Hi-Low 1000 Liquid system with its excellent release factors into a blend of solvents which were blended for their ability to remove most waxes from a mold surface. Relieves wax build up and may be used as an interphase item with the wax system for prolonged releases and cleaner, sharper molds and parts. It does not relieve styrene burns.

APPLICATION

Apply # 69 over a controlled area, saturate cloth with product, apply to surface, agitate thoroughly, wipe dry while still damp. Continue in this manner until entire mold has been treated.

Reapply a light even coat to assure a non-waxy, greaseless, non-porous surface. Wipe.

NOTE: IN THE EVENT OF HEAVY WAX BUILD UP continue to wash down mold with # 69 after every 2-4 cycles until you are sure that all waxes and contamination have disappeared from the pores of the gel coat.

1 Gallon covers 1262 square meters.

TYPICAL PHYSICAL CHARACTERISTICS

Weight:	7 lbs per gallon
Flash Point:	112° F
Shelf life:	1 year from date of shipment
V.O.C.:	7 lbs per gallon

FINISH KARE'S LIMITATIONS OF LIABILITY

To the best of our knowledge, the data presented here is true and accurate, but is subject to change without prior notice. User is kindly requested to contact Finish Kare Products to verify the correctness before specifying or ordering. Since we don't know how the product will be used we cannot assume any responsibility for its use, performance, or any injuries resulting from its use. Liability, if any, is limited to replacement of defective product. NO WARRANTY OR GUARANTEE OF ANY KIND IS EXPRESSED OR IMPLIED BY FINISH KARE PRODUCTS, INC.